



## Data sheet

### Simply better IROC® SR for pitched roofs

The rail system is suitable for corrugated sheet roofs, pantile roofs and metal roofs. By means of a cross-connection, IROC® SR is also ideally suited for transverse mounting in addition to upright mounting. The module clips can be used at any point on the profile, ensuring absolute flexibility in module mounting. The roof hooks can be attached from the side or from below.

### Advantages:

- ✓ Structurally proven components
- ✓ Fast assembly
- ✓ Minimal use of materials
- ✓ Suitable for all module types
- ✓ Cross mounting possible
- ✓ Module clips already pre-assembled
- ✓ Profile standard lengths 4.880 mm and 2.440 mm
- ✓ Can be used for span lengths up to 2.40 meters

<b>Mounting type</b>	Roof parallel
<b>Profile length</b>	Standard: 4.880 mm and 2.440 mm
<b>Module size</b>	For all common module types, also suitable for unframed modules
<b>Module orientation</b>	Vertical and / or transverse mounting
<b>Roof covering</b>	Pantiled roof, corrugated sheet roof, standing seam roof, Kalzip roof
<b>Material</b>	Aluminum, screw connections and roof anchors V2A
<b>Connection</b>	Roof hooks, hanger bolts, Kalzip clamp, sheet metal seam clamp
<b>Requirements</b>	The load-bearing capacity of the roof and the roof insulation must be checked and guaranteed by the customer.

